



GHS Compliance Labels **New!**

Meets New OSHA GHS HazCom Standard & Includes Required SDS Information

PRODUCT IDENTIFIER
CODE _____
Product Name: LIQUEFIED PETROLEUM GAS (LPG) PROPANE

HAZARD PICTOGRAMS

SIGNAL WORD
DANGER

HAZARD STATEMENT
Extremely flammable gas.
Contains gas under pressure, may explode if heated.
May cause damage to central nervous and respiratory systems.

SUPPLIER IDENTIFICATION
Company Name _____
Street Address _____
City _____ State _____
Postal Code _____ Country _____
Emergency Phone Number _____

PRECAUTIONARY STATEMENTS
Prevention:
1. Keep away from heat/spark/open flame/hot surfaces. No smoking.
2. Do not breathe fumes/gas/aerosol/vapors/mists/sprays/liquids/aerosols.
3. Wash thoroughly after handling.
4. Do not eat, drink or smoke when using this product.
Response:
1. Lacking gas flow. Do not extinguish, unless leak can be stopped safely. Evacuate all ignition sources if safe to do so.
2. If exposed or concerned. Call a POISON CENTER or doctor/hospital.
Storage:
1. Protect from sunlight. Store in a well-ventilated place.
2. In case of contact with skin, hot areas open to allow heat to dissipate. Contact with compressed gas cylinders may irritate. Remove contaminated clothing. Use of clothing made of loose fabric may increase irritant absorption. Risk of explosion is extremely low. However, if an explosive atmosphere is formed, wearing protective clothing is essential to keep as far as possible from any ignition source. If necessary, provide sufficient oxygen flow to avoid suffocation. Do not use compressed gas cylinders unnecessarily.

FIRST AID
In case of contact with skin, hot areas open to allow heat to dissipate. Contact with compressed gas cylinders may irritate. Remove contaminated clothing. Use of clothing made of loose fabric may increase irritant absorption. Risk of explosion is extremely low. However, if an explosive atmosphere is formed, wearing protective clothing is essential to keep as far as possible from any ignition source. If necessary, provide sufficient oxygen flow to avoid suffocation. Do not use compressed gas cylinders unnecessarily.

IN CASE OF FIRE
GENERAL FIRE HAZARD: See Section 9 for Flammability Properties. Liquid releases flammable vapors and will become ambient temperature and readily forms a flammable mixture with air. Dangerous for and outside hazard when exposed to heat, sparks or flame. Vapors are heavier than air and may travel long distance to a point of ignition and flash back.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

EXTINGUISHING MEDIA: Use extinguishing media suitable for the surrounding material, preferably not any extinguisher suitable for Class B fires, dry chemical, fog fighting foam, CO₂, and other gaseous agents. However, fog should not be extinguished unless flow of gas can be immediately stopped.

UNSTABLE/EXTRINSIC MEDIA: None.

LPG - Propane

PRODUCT IDENTIFIER
CODE _____
Product Name: GASOLINE ALL GRADES

HAZARD PICTOGRAMS

SIGNAL WORD
DANGER

HAZARD STATEMENT
Highly flammable liquid and vapor.
Causes skin irritation.
May cause genetic defects.
May cause cancer.
May damage fertility or the unborn child.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to aquatic life, kidneys, bladder, blood, bone marrow, nervous system through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Hazardous to aquatic life.

SUPPLIER IDENTIFICATION
Company Name _____
Street Address _____
City _____ State _____
Postal Code _____ Country _____
Emergency Phone Number _____

PRECAUTIONARY STATEMENTS
Prevention:
1. Keep away from heat/spark/open flame/hot surfaces. No smoking.
2. Keep container tightly closed.
3. Grounded container and working equipment.
4. Use explosion-proof electrical/ventilating/lighting/equipment.
5. Use only non-sparking tools.
6. Non-combustible. Electric spark may cause discharge.
7. Wear protective gloves/protective clothing/eye protection/face shield.
8. Wash hands and face thoroughly after handling.
9. Obtain special instructions before use.
10. Do not handle until all safety procedures have been read and understood.
11. Do not breathe mist/vapors/aerosols.
12. Use only outdoors or in well-ventilated area.
13. Do not eat, drink or smoke when using this product.
14. Avoid release to the environment.

FIRST AID
In case of contact with skin, immediately flush with clean, lukewarm water for at least 15 min. Hot water may increase absorption. Do not rub. Do not use solvents. Remove contaminated clothing. Wash thoroughly with soap and water or with solvent hand cleaner. Skin: Medical attention if irritation or severe burning. DO NOT INDUCE VOMITING. Do not give fluids. Other immediate medical attention if symptoms develop. Do not induce vomiting unless directed by medical personnel. Small amount of residue which can be easily removed by washing with soap and water. Do not use petroleum solvents. If necessary, provide artificial respiration. Avoid breathing vapors. Avoid contact with eyes. Wash thoroughly with soap and water. Do not use artificial respiration.

IN CASE OF FIRE
SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fog fighting foam, or gaseous extinguishing agent.
LARGE FIRES: Water spray, fog or fog fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire exposed containers. Fighting foam suitable for polar solvents is recommended for heat with greater than 10% oxygen concentration.

Gasoline - All Types

PRODUCT IDENTIFIER
CODE _____
Product Name: DIESEL FUEL ALL TYPES

HAZARD PICTOGRAMS

SIGNAL WORD
DANGER

HAZARD STATEMENT
Flammable liquid and vapor.
Causes skin irritation.
Suspected of causing genetic defects.
Suspected of causing cancer.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Hazardous to aquatic life.

SUPPLIER IDENTIFICATION
Company Name _____
Street Address _____
City _____ State _____
Postal Code _____ Country _____
Emergency Phone Number _____

PRECAUTIONARY STATEMENTS
Prevention:
1. Keep away from heat/spark/open flame/hot surfaces. No smoking.
2. Keep container tightly closed.
3. Grounded container and working equipment.
4. Use explosion-proof electrical/equipment.
5. Use only non-sparking tools.
6. Take precautionary measures against static discharge.
7. Wear protective gloves/protective clothing/eye protection/face shield.
8. Wash hands and face thoroughly after use.
9. Obtain special instructions before use.
10. Do not handle until all safety procedures have been read and understood.
11. Avoid breathing fumes/mist/vapors/sprays.

FIRST AID
In case of contact with skin, immediately flush with clean, lukewarm water for at least 15 min. Hot water may increase absorption. Do not rub. Do not use solvents. Remove contaminated clothing. Wash thoroughly with soap and water or with solvent hand cleaner. Skin: Medical attention if irritation or severe burning. DO NOT INDUCE VOMITING. Do not give fluids. Other immediate medical attention if symptoms develop. Do not induce vomiting unless directed by medical personnel. Small amount of residue which can be easily removed by washing with soap and water. Do not use petroleum solvents. If necessary, provide artificial respiration. Avoid breathing vapors. Avoid contact with eyes. Wash thoroughly with soap and water. Do not use artificial respiration.

IN CASE OF FIRE
SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fog fighting foam, and other gaseous agents.
LARGE FIRES: Water spray, fog or fog fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire exposed containers.

Diesel - All Types

PRODUCT IDENTIFIER
CODE _____
Product Name: _____

HAZARD PICTOGRAMS

SIGNAL WORD
DANGER

HAZARD STATEMENT

SUPPLIER IDENTIFICATION
Company Name _____
Street Address _____
City _____ State _____
Postal Code _____ Country _____
Emergency Phone Number _____

PRECAUTIONARY STATEMENTS
Prevention:
1. _____
2. _____
3. _____
4. _____
5. _____
6. _____
7. _____
8. _____
9. _____
10. _____
11. _____

FIRST AID
In case of contact with skin, immediately flush with clean, lukewarm water for at least 15 min. Hot water may increase absorption. Do not rub. Do not use solvents. Remove contaminated clothing. Wash thoroughly with soap and water or with solvent hand cleaner. Skin: Medical attention if irritation or severe burning. DO NOT INDUCE VOMITING. Do not give fluids. Other immediate medical attention if symptoms develop. Do not induce vomiting unless directed by medical personnel. Small amount of residue which can be easily removed by washing with soap and water. Do not use petroleum solvents. If necessary, provide artificial respiration. Avoid breathing vapors. Avoid contact with eyes. Wash thoroughly with soap and water. Do not use artificial respiration.

IN CASE OF FIRE
SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fog fighting foam, and other gaseous agents.
LARGE FIRES: Water spray, fog or fog fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire exposed containers.

Blank

Each label is 5" x 7", printed on specially laminated, UV and weather resistant vinyl for outdoor posting! Can be written on with Sharpie pens.

NEW GHS Haz/Com Compliant Labels for typical jobsite products. Each label includes the appropriate GHS Pictogram, Product Identifier, Precautionary Statements, First Aid, Fire Protection, Signal Word, Hazard Statements, Supplier Identification area and Supplemental Information area. (Supplier and supplemental info must be filled in by user. Blank labels require all information to be filled in by user.)

ORDERING INFORMATION

Quantity	AGC Member Unit Price	Non-Member Unit Price	Total
LPG	\$1 per label.	\$5 per label.	\$
GAS			\$
Diesel			\$
Blank			\$
Add: Shipping \$5 for the first 25 labels. \$1 for each 10 label increment thereafter.			\$
Sub-total			\$
Specify County: _____ Add Applicable Sales Tax			\$
Total Due			\$

Please complete and return this form by mail or fax to:
AGC NYS, LLC
10 Airline Drive, Suite 203
Albany, NY 12205
Phone: (518) 456-1134
Fax: (518) 456-1198

Min. order of 10 Any mix of style.

Please include method of payment with your order:

Check payable to AGC NYS, LLC Visa/MC/AmEx # _____ Exp. Date _____/_____/_____

Billing Street # _____ Zip _____ CVV Code _____ Signature _____

Ship To: Company Name _____ Contact/Dept. _____

Street _____

City, State, Zip _____

Phone _____ Fax _____

THIS IS YOUR INVOICE - PLEASE PAY FROM ORDER FORM.

Effective January, 2014